

The top of the page features a decorative graphic on the left with overlapping teal and grey squares of various sizes. The text 'CreativeRealities' is overlaid on this graphic, with 'Creative' in white and 'Realities' in teal. To the right, a photograph shows a thermal mirror kiosk in a modern building lobby. The kiosk is a vertical silver pole with a smartphone mounted on it, displaying a woman's face. The background shows large glass windows and a view of a city with a distinctive geodesic dome structure.

CreativeRealities

Thermal Mirror Specifications Sheet

Please contact us at clientexperience@cri.com
or: 1-888-323-3633 at any time.

Display	<ul style="list-style-type: none"> • 8 inch, LCD IPS Display (Non-touch), Screen resolution: 800 x 1280
Processor	<ul style="list-style-type: none"> • ARM Quad Core, A17 1.8 Ghz
Memory	<ul style="list-style-type: none"> • DDR 2GB, eMMC Flash 8GB
Camera	<ul style="list-style-type: none"> • Dual lens Stereo camera • 2 MegaPixels, Auto White Balance • Dual IR sensor • Focus Distance: 1.6 ~ 4.9ft (Auto)
Thermal Image Sensor	<ul style="list-style-type: none"> • Optimal distance: 1.6 ~ 3ft • 32 x 32 Pixels • Accuracy: +/- 0.9°F • Field of view: 89.6 degree • Temperature Measurement Range: 50°F ~ 107.6°F
Features	<ul style="list-style-type: none"> • Employee Validation • Visitor Mode (Configurable) • Mask Mode (Configurable) • Alarms: Unknown Visitor, No Mask, High Temperature • Stand Alone (Non-network) Use: Supported
Performance	<ul style="list-style-type: none"> • Temperature Measurement Speed: 1-2 sec
Operating System	<ul style="list-style-type: none"> • Android 7.1 Nougat
Ports and Interfaces	<ul style="list-style-type: none"> • 1 x USB 2.0 • Serial: RS232 • Relay: Door Open Signal • Wiegand: 26/34 Input/Output
Audio	<ul style="list-style-type: none"> • 2.5W rear speakers
Connectivity	<ul style="list-style-type: none"> • RJ45 1000M Ethernet Interface, Built-in WiFi
Physical Dimension	<ul style="list-style-type: none"> • Overall: 11.8" H x 5.25" W x 0.9" D • Pole Mount: Adds 3.5" D & 2.7" H • Weight: 2.5 lbs.
Power Supply	<ul style="list-style-type: none"> • DC 12V adapter, PoE+, Power Consumption: 13.5W
Mounting	<ul style="list-style-type: none"> • Gate/Counter: From pole, using locking nut • Wall: Using adapter • Floor: Using adapter
Certifications	<ul style="list-style-type: none"> • FCC, CE, UL Power

Please contact us at clientexperience@cri.com or: 1-888-323-3633 at any time.